



國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-001	0.74	2.78	1.02
AS568-002	1.07	3.61	1.27
AS568-003	1.42	4.48	1.53
AS568-004	1.78	5.34	1.78
AS568-005	2.57	6.13	1.78
AS568-006	2.90	6.46	1.78
AS568-007	3.69	7.25	1.78
AS568-008	4.47	8.03	1.78
AS568-009	5.29	8.85	1.78
AS568-010	6.07	9.63	1.78
AS568-011	7.65	11.21	1.78
AS568-012	9.25	12.81	1.78
AS568-013	10.82	14.38	1.78
AS568-014	12.42	15.98	1.78
AS568-015	14.00	17.56	1.78
AS568-016	15.60	19.16	1.78
AS568-017	17.17	20.73	1.78
AS568-018	18.77	22.33	1.78
AS568-019	20.35	23.91	1.78
AS568-020	21.95	25.51	1.78
AS568-021	23.52	27.08	1.78
AS568-022	25.12	28.68	1.78

國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-023	26.70	30.26	1.78
AS568-024	28.30	31.86	1.78
AS568-025	29.87	33.43	1.78
AS568-026	31.47	35.03	1.78
AS568-027	33.05	36.61	1.78
AS568-028	34.65	38.21	1.78
AS568-029	37.82	41.38	1.78
AS568-030	41.00	44.56	1.78
AS568-031	44.17	47.73	1.78
AS568-032	47.35	50.91	1.78
AS568-033	50.52	54.08	1.78
AS568-034	53.70	57.26	1.78
AS568-035	56.87	60.43	1.78
AS568-036	60.04	63.60	1.78
AS568-037	63.22	66.78	1.78
AS568-038	66.40	69.96	1.78
AS568-039	69.57	73.13	1.78
AS568-040	72.75	76.31	1.78
AS568-041	75.92	79.48	1.78
AS568-042	82.27	85.83	1.78
AS568-043	88.62	92.18	1.78
AS568-044	94.97	98.53	1.78



國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-045	101.32	104.88	1.78
AS568-046	107.62	111.18	1.78
AS568-047	114.02	117.58	1.78
AS568-048	120.37	123.93	1.78
AS568-049	126.72	130.28	1.78
AS568-050	133.07	136.63	1.78
AS568-102	1.24	6.48	2.62
AS568-103	2.05	7.29	2.62
AS568-104	2.84	8.08	2.62
AS568-105	3.63	8.87	2.62
AS568-106	4.42	9.66	2.62
AS568-107	5.23	10.47	2.62
AS568-108	6.02	11.26	2.62
AS568-109	7.60	12.84	2.62
AS568-110	9.19	14.43	2.62
AS568-111	10.77	16.01	2.62
AS568-112	12.37	17.61	2.62
AS568-113	13.95	19.19	2.62
AS568-114	15.54	20.78	2.62
AS568-115	17.12	22.36	2.62
AS568-116	18.72	23.96	2.62
AS568-117	20.29	25.53	2.62
AS568-118	21.90	27.14	2.62
AS568-119	23.47	28.71	2.62
AS568-120	25.07	30.31	2.62
AS568-121	26.65	31.89	2.62
AS568-122	28.25	33.49	2.62
AS568-123	29.82	35.06	2.62
AS568-124	31.42	36.66	2.62
AS568-125	32.99	38.23	2.62
AS568-126	34.60	39.84	2.62
AS568-127	36.17	41.41	2.62
AS568-128	37.77	43.01	2.62
AS568-129	39.35	44.59	2.62
AS568-130	40.95	46.19	2.62

國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-131	42.52	47.76	2.62
AS568-132	44.12	49.36	2.62
AS568-133	45.70	50.94	2.62
AS568-134	47.30	52.54	2.62
AS568-135	48.90	54.14	2.62
AS568-136	50.47	55.71	2.62
AS568-137	52.07	57.31	2.62
AS568-138	53.65	58.89	2.62
AS568-139	55.25	60.49	2.62
AS568-140	56.82	62.06	2.62
AS568-141	58.42	63.66	2.62
AS568-142	60.00	65.24	2.62
AS568-143	61.60	66.84	2.62
AS568-144	63.17	68.41	2.62
AS568-145	64.77	70.01	2.62
AS568-146	66.35	71.59	2.62
AS568-147	67.95	73.19	2.62
AS568-148	69.52	74.76	2.62
AS568-149	71.12	76.36	2.62
AS568-150	72.70	77.94	2.62
AS568-151	75.87	81.11	2.62
AS568-152	82.22	87.46	2.62
AS568-153	88.57	93.81	2.62
AS568-154	94.92	100.16	2.62
AS568-155	101.27	106.51	2.62
AS568-156	107.62	112.86	2.62
AS568-157	113.97	119.21	2.62
AS568-158	120.32	125.56	2.62
AS568-159	126.67	131.91	2.62
AS568-160	133.02	138.26	2.62
AS568-161	139.37	144.61	2.62
AS568-162	145.72	150.96	2.62
AS568-163	152.07	157.31	2.62
AS568-164	158.42	163.66	2.62
AS568-165	164.77	170.01	2.62



國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-166	171.12	176.36	2.62
AS568-167	177.47	182.71	2.62
AS568-168	183.82	189.06	2.62
AS568-169	190.17	195.41	2.62
AS568-170	196.52	201.76	2.62
AS568-171	202.87	208.11	2.62
AS568-172	209.22	214.46	2.62
AS568-173	215.57	220.81	2.62
AS568-174	221.92	227.16	2.62
AS568-175	228.27	233.51	2.62
AS568-176	234.62	239.86	2.62
AS568-177	240.97	246.21	2.62
AS568-178	247.32	252.56	2.62
AS568-201	4.34	11.40	3.53
AS568-202	5.94	13.00	3.53
AS568-203	7.52	14.58	3.53
AS568-204	9.12	16.18	3.53
AS568-205	10.69	17.75	3.53
AS568-206	12.29	19.35	3.53
AS568-207	13.87	20.93	3.53
AS568-208	15.47	22.53	3.53
AS568-209	17.04	24.10	3.53
AS568-210	18.64	25.70	3.53
AS568-211	20.22	27.28	3.53
AS568-212	21.82	28.88	3.53
AS568-213	23.40	30.46	3.53
AS568-214	25.00	32.06	3.53
AS568-215	26.57	33.63	3.53
AS568-216	28.17	35.23	3.53
AS568-217	29.75	36.81	3.53
AS568-218	31.34	38.40	3.53
AS568-219	32.92	39.98	3.53
AS568-220	34.52	41.58	3.53
AS568-221	36.10	43.16	3.53
AS568-222	37.70	44.76	3.53

國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-223	40.87	47.93	3.53
AS568-224	44.05	51.11	3.53
AS568-225	47.22	54.28	3.53
AS568-226	50.40	57.46	3.53
AS568-227	53.57	60.63	3.53
AS568-228	56.75	63.81	3.53
AS568-229	59.92	66.98	3.53
AS568-230	63.10	70.16	3.53
AS568-231	66.27	73.33	3.53
AS568-232	69.44	76.50	3.53
AS568-233	72.62	79.68	3.53
AS568-234	75.79	82.85	3.53
AS568-235	78.97	86.03	3.53
AS568-236	82.14	89.20	3.53
AS568-237	85.32	92.38	3.53
AS568-238	88.49	95.55	3.53
AS568-239	91.67	98.73	3.53
AS568-240	94.84	101.90	3.53
AS568-241	98.02	105.08	3.53
AS568-242	101.19	108.25	3.53
AS568-243	104.37	111.43	3.53
AS568-244	107.54	114.60	3.53
AS568-245	110.72	117.78	3.53
AS568-246	113.89	120.95	3.53
AS568-247	117.07	124.13	3.53
AS568-248	120.24	127.30	3.53
AS568-249	123.42	130.48	3.53
AS568-250	126.59	133.65	3.53
AS568-251	129.77	136.83	3.53
AS568-252	132.94	140.00	3.53
AS568-253	136.12	143.18	3.53
AS568-254	139.30	146.36	3.53
AS568-255	142.47	149.53	3.53
AS568-256	145.65	152.71	3.53
AS568-257	148.82	155.88	3.53



國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-258	152.00	159.06	3.53
AS568-259	158.35	165.41	3.53
AS568-260	164.70	171.76	3.53
AS568-261	171.05	178.11	3.53
AS568-262	177.40	184.46	3.53
AS568-263	183.75	190.81	3.53
AS568-264	190.10	197.16	3.53
AS568-265	196.45	203.51	3.53
AS568-266	202.80	209.86	3.53
AS568-267	209.15	216.21	3.53
AS568-268	215.50	222.56	3.53
AS568-269	221.85	228.91	3.53
AS568-270	228.20	235.26	3.53
AS568-271	234.55	241.61	3.53
AS568-272	240.90	247.96	3.53
AS568-273	247.25	254.31	3.53
AS568-274	253.60	260.66	3.53
AS568-275	266.30	273.36	3.53
AS568-276	279.00	286.06	3.53
AS568-277	291.70	298.76	3.53
AS568-278	304.40	311.46	3.53
AS568-279	329.80	336.86	3.53
AS568-280	355.20	362.26	3.53
AS568-281	380.60	387.66	3.53
AS568-282	405.26	412.32	3.53
AS568-283	430.66	437.72	3.53
AS568-284	456.06	463.12	3.53
AS568-309	10.46	21.12	5.33
AS568-310	12.07	22.73	5.33
AS568-311	13.64	24.30	5.33
AS568-312	15.24	25.90	5.33
AS568-313	16.81	27.47	5.33
AS568-314	18.42	29.08	5.33
AS568-315	19.99	30.65	5.33
AS568-316	21.59	32.25	5.33

國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-317	23.16	33.82	5.33
AS568-318	24.77	35.43	5.33
AS568-319	26.34	37.00	5.33
AS568-320	27.94	38.60	5.33
AS568-321	29.51	40.17	5.33
AS568-322	31.12	41.78	5.33
AS568-323	32.69	43.35	5.33
AS568-324	34.29	44.95	5.33
AS568-325	37.47	48.13	5.33
AS568-326	40.65	51.31	5.33
AS568-327	43.82	54.48	5.33
AS568-328	46.99	57.65	5.33
AS568-329	50.16	60.82	5.33
AS568-330	53.34	64.00	5.33
AS568-331	56.52	67.18	5.33
AS568-332	59.69	70.35	5.33
AS568-333	62.87	73.53	5.33
AS568-334	66.04	76.70	5.33
AS568-335	69.22	79.88	5.33
AS568-336	72.39	83.05	5.33
AS568-337	75.57	86.23	5.33
AS568-338	78.74	89.40	5.33
AS568-339	81.92	92.58	5.33
AS568-340	85.09	95.75	5.33
AS568-341	88.27	98.93	5.33
AS568-342	91.44	102.10	5.33
AS568-343	94.62	105.28	5.33
AS568-344	97.79	108.45	5.33
AS568-345	100.96	111.62	5.33
AS568-346	104.14	114.80	5.33
AS568-347	107.32	117.98	5.33
AS568-348	110.49	121.15	5.33
AS568-349	113.67	124.33	5.33
AS568-350	116.84	127.50	5.33
AS568-351	120.02	130.68	5.33



國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-352	123.19	133.85	5.33
AS568-353	126.37	137.03	5.33
AS568-354	129.54	140.20	5.33
AS568-355	132.72	143.38	5.33
AS568-356	135.89	146.55	5.33
AS568-357	139.07	149.73	5.33
AS568-358	142.24	152.90	5.33
AS568-359	145.42	156.08	5.33
AS568-360	148.59	159.25	5.33
AS568-361	151.77	162.43	5.33
AS568-362	158.12	168.78	5.33
AS568-363	164.47	175.13	5.33
AS568-364	170.82	181.48	5.33
AS568-365	177.17	187.83	5.33
AS568-366	183.52	194.18	5.33
AS568-367	189.87	200.53	5.33
AS568-368	196.22	206.88	5.33
AS568-369	202.57	213.23	5.33
AS568-370	208.92	219.58	5.33
AS568-371	215.27	225.93	5.33
AS568-372	221.62	232.28	5.33
AS568-373	227.97	238.63	5.33
AS568-374	234.32	244.98	5.33
AS568-375	240.67	251.33	5.33
AS568-376	247.02	257.68	5.33
AS568-377	253.37	264.03	5.33
AS568-378	266.07	276.73	5.33
AS568-379	278.77	289.43	5.33
AS568-380	291.47	302.13	5.33
AS568-381	304.17	314.83	5.33
AS568-382	329.55	340.21	5.33
AS568-383	354.97	365.63	5.33
AS568-384	380.37	391.03	5.33
AS568-385	405.26	415.92	5.33
AS568-386	430.65	441.31	5.33

國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-387	456.06	466.72	5.33
AS568-388	481.46	492.12	5.33
AS568-389	506.86	517.52	5.33
AS568-390	532.26	542.92	5.33
AS568-391	557.66	568.32	5.33
AS568-392	582.65	593.31	5.33
AS568-393	608.10	618.76	5.33
AS568-394	633.50	644.16	5.33
AS568-395	658.85	669.51	5.33
AS568-425	113.67	127.65	6.99
AS568-426	116.84	130.82	6.99
AS568-427	120.02	134.00	6.99
AS568-428	123.19	137.17	6.99
AS568-429	126.37	140.35	6.99
AS568-430	129.54	143.52	6.99
AS568-431	132.72	146.70	6.99
AS568-432	135.89	149.87	6.99
AS568-433	139.07	153.05	6.99
AS568-434	142.24	156.22	6.99
AS568-435	145.42	159.40	6.99
AS568-436	148.59	162.57	6.99
AS568-437	151.77	165.75	6.99
AS568-438	158.12	172.10	6.99
AS568-439	164.47	178.45	6.99
AS568-440	170.82	184.80	6.99
AS568-441	177.17	191.15	6.99
AS568-442	183.52	197.50	6.99
AS568-443	189.87	203.85	6.99
AS568-444	196.22	210.20	6.99
AS568-445	202.57	216.55	6.99
AS568-446	215.27	229.25	6.99
AS568-447	227.97	241.95	6.99
AS568-448	240.67	254.65	6.99
AS568-449	253.37	267.35	6.99
AS568-450	266.07	280.05	6.99



國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-451	278.77	292.75	6.99
AS568-452	291.47	305.45	6.99
AS568-453	304.17	318.15	6.99
AS568-454	316.87	330.85	6.99
AS568-455	329.57	343.55	6.99
AS568-456	342.27	356.25	6.99
AS568-457	354.97	368.95	6.99
AS568-458	367.67	381.65	6.99
AS568-459	380.37	394.35	6.99
AS568-460	393.07	407.05	6.99
AS568-461	405.26	419.24	6.99
AS568-462	417.96	431.94	6.99
AS568-463	430.66	444.64	6.99
AS568-464	443.36	457.34	6.99
AS568-465	456.06	470.04	6.99
AS568-466	468.76	482.74	6.99
AS568-467	481.46	495.44	6.99
AS568-468	494.16	508.14	6.99
AS568-469	506.86	520.84	6.99
AS568-470	532.26	546.24	6.99
AS568-471	557.66	571.64	6.99
AS568-472	582.65	596.63	6.99
AS568-473	608.10	622.08	6.99
AS568-474	633.50	647.48	6.99
AS568-475	658.85	672.83	6.99
AS568-901	4.70	7.54	1.42
AS568-902	6.07	9.33	1.63
AS568-903	7.65	10.91	1.63
AS568-904	8.92	12.58	1.83
AS568-905	10.52	14.18	1.83
AS568-906	11.89	15.85	1.98
AS568-907	13.46	17.62	2.08
AS568-908	16.36	20.78	2.21
AS568-909	17.94	22.86	2.46
AS568-910	19.18	24.10	2.46

國際規格	ID(內徑)	OD(外徑)	W(線徑)
AS568-911	21.92	27.82	2.95
AS568-912	23.47	29.37	2.95
AS568-913	25.04	30.94	2.95
AS568-914	26.60	32.50	2.95
AS568-916	29.75	35.65	2.95
AS568-918	34.42	40.32	2.95
AS568-920	37.46	43.46	3.00
AS568-924	43.68	49.68	3.00
AS568-928	53.09	59.09	3.00
AS568-932	59.36	65.36	3.00

