



國際規格	ID(內徑)	OD(外徑)	W(線徑)
P2	1.8	5.6	1.9
P3	2.8	6.6	1.9
P4	3.8	7.6	1.9
P5	4.8	8.6	1.9
P6	5.8	9.6	1.9
P7	6.8	10.6	1.9
PS	7.8	11.6	1.9
PG	8.8	12.6	1.9
P 10	9.8	13.6	1.9
P10A	9.8	14.6	2.4
P 11	10.8	15.6	2.4
P 11.2	11	15.8	2.4
P 12	11.8	16.6	2.4
P 12.5	12.3	17.1	2.4
P 14	13.8	18.6	2.4
P15	14.8	19.6	2.4
P 16	15.8	20.6	2.4
P 17	16.8	21.6	2.4
P 18	17.8	22.6	2.4
P 19	18.8	23.6	2.4
P 20	19.8	24.6	2.4
P 21	20.8	25.6	2.4
P 22	21.8	26.6	2.4
P 22A	21.7	28.7	3.5
P 22.4	22.1	29.1	3.5
P 24	23.7	30.7	3.5

國際規格	ID(內徑)	OD(外徑)	W(線徑)
P 25	24.7	31.7	3.5
P 25.5	25.2	32.2	3.5
P 26	25.7	32.7	3.5
P 28	27.7	34.7	3.5
P 29	28.7	35.7	3.5
P 29.5	29.2	36.2	3.5
P 30	29.7	36.7	3.5
P 31	30.7	37.7	3.5
P31.5	31.2	38.2	3.5
P 32	31.7	38.7	3.5
P 34	33.7	40.7	3.5
P 35	34.7	41.7	3.5
P35.5	35.2	42.2	3.5
P 36	35.7	42.7	3.5
P 38	37.7	44.7	3.5
P 39	38.7	45.7	3.5
P40	39.7	46.7	3.5
P 41	40.7	47.7	3.5
P42	41.7	48.7	3.5
P44	43.7	50.7	3.5
P45	44.7	51.7	3.5
P46	45.7	52.7	3.5
P47A	47	58.4	5.7
P48	47.7	54.7	3.5
P48A	47.6	59	5.7
P49	48.7	55.7	3.5



國際規格	ID(內徑)	OD(外徑)	W(線徑)
P 50	49.7	56.7	3.5
P 50A	49.6	61	5.7
P 52	51.6	63	5.7
P 53	52.6	64	5.7
P 55	54.6	66	5.7
P 56	55.6	67	5.7
P 58	57.6	69	5.7
P 60	59.6	71	5.7
P 62	61.6	73	5.7
P 63	62.6	74	5.7
P 65	64.6	76	5.7
P 67	66.6	78	5.7
P 70	69.6	81	5.7
P 71	70.6	82	5.7
P 75	74.6	86	5.7
P 80	79.6	91	5.7
P 85	84.6	96	5.7
P 90	89.6	101	5.7
P 95	94.6	106	5.7
P 100	99.6	111	5.7
P 102	101.6	113	5.7
P 105	104.6	116	5.7
P 110	109.6	121	5.7
P 112	111.6	123	5.7
P 115	114.6	126	5.7
P 120	119.6	131	5.7
P 125	124.6	136	5.7
P 130	129.6	141	5.7
P 132	131.6	143	5.7
P 135	134.6	146	5.7
P 140	139.6	151	5.7
P 145	144.6	156	5.7
P 150	149.6	161	5.7
P 150A	149.5	166.3	8.4
P 155	154.5	171.3	8.4
P 160	159.5	176.3	8.4
P 165	164.5	181.3	8.4
P170	169.5	186.3	8.4

國際規格	ID(內徑)	OD(外徑)	W(線徑)
P 175	174.5	191.3	8.4
P 180	179.5	196.3	8.4
P 185	184.5	201.3	8.4
P 190	189.5	206.3	8.4
P 195	194.5	211.3	8.4
P 200	199.5	216.3	8.4
P 205	204.5	221.3	8.4
P 209	208.5	225.3	8.4
P 210	209.5	226.3	8.4
P 215	214.5	231.3	8.4
P 220	219.5	236.3	8.4
P 225	224.5	241.3	8.4
P 230	229.5	246.3	8.4
P 235	234.5	251.3	8.4
P 240	239.5	256.3	8.4
P 245	244.5	261.3	8.4
P 250	249.5	266.3	8.4
P 255	254.5	271.3	8.4
P 260	259.5	276.3	8.4
P 265	264.5	281.3	8.4
P 270	269.5	286.3	8.4
P 275	274.5	291.3	8.4
P 280	279.5	296.3	8.4
P 285	284.5	301.3	8.4
P 290	289.5	306.3	8.4
P 295	294.5	311.3	8.4
P 300	299.5	316.3	8.4
P 305	304.5	321.3	8.4
P 310	309.5	326.3	8.4
P 315	314.5	331.3	8.4
P 320	319.5	336.3	8.4
P 325	324.5	341.3	8.4
P 330	329.5	346.3	8.4
P 335	334.5	351.3	8.4
P 340	339.5	356.3	8.4
P 345	344.5	361.3	8.4
P 350	349.5	366.3	8.4
P 355	354.5	371.3	8.4



國際規格	ID(內徑)	OD(外徑)	W(線徑)
P 360	359.5	376.3	8.4
P 365	364.5	381.3	8.4
P 370	369.5	386.3	8.4
P 375	374.5	391.3	8.4
P 380	379.5	396.3	8.4
P 385	384.5	401.3	8.4
P 390	389.5	406.3	8.4
P 395	394.5	411.3	8.4
P 400	399.5	416.3	8.4
P 405	404.5	421.3	8.4
P 410	409.5	426.3	8.4
P 415	414.5	431.3	8.4
P 420	419.5	436.3	8.4
P 425	424.5	441.3	8.4
P 430	429.5	446.3	8.4
P 435	434.5	451.3	8.4
P440	439.5	456.3	8.4
P445	444.5	461.3	8.4
P 450	449.5	466.3	8.4
P 455	454.5	471.3	8.4
P 460	459.5	476.3	8.4
P 465	464.5	481.3	8.4
P 470	469.5	486.3	8.4
P 475	474.5	491.3	8.4
P 480	479.5	496.3	8.4
P 485	484.5	501.3	8.4
P 490	489.5	506.3	8.4
P 495	494.5	511.3	8.4
P 500	499.5	516.3	8.4
P 505	504.5	521.3	8.4
P 510	509.5	526.3	8.4
P 515	514.5	531.3	8.4
P 520	519.5	536.3	8.4
P 525	524.5	541.3	8.4
P 530	529.5	546.3	8.4

國際規格	ID(內徑)	OD(外徑)	W(線徑)
P 535	534.5	551.3	8.4
P 540	539.5	556.3	8.4
P 545	544.5	561.3	8.4
P 550	549.5	566.3	8.4
P 555	554.5	571.3	8.4
P 560	559.5	576.3	8.4
P 565	564.5	581.3	8.4
P 570	569.5	586.3	8.4
P 575	574.5	591.3	8.4
P 580	579.5	596.3	8.4
P 585	584.5	601.3	8.4
P 590	589.5	606.3	8.4
P 595	594.5	611.3	8.4
P 600	599.5	616.3	8.4

